



JOYA™ TOUCH A6 IS THE MULTI-PURPOSE DEVICE FOR RETAIL

The new Joya Touch A6 device for use in retail will optimize your ROI and is designed for applications in Self-Shopping, Shop Floor, Access Control and more.

MULTIPLE DEVICES IN ONE

The Joya Touch A6 device comes with a powerful Qualcomm Snapdragon platform and features Android™ 6.0 Marshmallow (field upgradeable to Android™ 7.1 Nougat). This device is available in two form factors: a handheld version resembling a smartphone and a pistol-grip version with a comfortable trigger. Users can change from one form to the other with ease, adapting to applications and user preferences.

WIRELESS CHARGING CRADLE – SINGLE AND 3-SLOT

The Joya Touch A6 device is charged using the industry's first wireless charging technology that eliminates the need for cleaning the contacts on the device and cradles. It radically reduces support costs and increases its life span.

The multi-bay cradle and single cradles support both handheld and pistol-grip models of the device, ensuring the right configuration for every use or application.

DIGIMARC® WATERMARKED BAR CODES

Joya Touch A6 is ready for the future being the first mobile computer to read Digimarc bar codes.

BOOST AND FAST CHARGING

The Joya Touch A6 device requires only 2 hours to fully charge the battery and the Boost Recharge feature ensures quick recharging. Six charging profiles are available to let the user decide which profile better suits their needs.

VOICE COMMUNICATOR

The Joya Touch A6 device can also be used as a phone using the Voice over Internet Protocol (VoIP), leveraging your Wi-Fi network.



FEATURES

- Multi-purpose device: handheld or pistol-grip
- Field upgradeable to Android 7.1 Nougat
- Wireless charging eliminates all contacts on the device and cradle
- Supports both Boost and Fast charging modes
- VoIP phone capabilities over Wi-Fi
- Reads Digimarc watermarked bar codes
- Presentation mode allows automatic scanning
- Datalogic SoftSpot™ technology for innovative triggering through the touch display
- 3-Axis Accelerometer auto-rotates the screen orientation
- 4.3 inch capacitive multi-touch FWVGA display with Gorilla® Glass 3
- Vibration alert for notifications
- Fully supports Datalogic's self-shopping middleware Shopevolution™ or third-party software
- Beacon support via BLE for geolocation
- Advanced 2D imaging technology
- Datalogic's patented 'Green Spot' technology for visual good-read feedback
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Retail:
 - Self-Shopping
 - Queue-Busting
 - Inventory
 - Access Control
 - Gift Registry
 - Shop Floor Applications
 - Assisted Sales

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS

| | |
|------------------------------|--|
| LOCAL AREA NETWORK (WLAN) | IEEE 802.11 a/b/g/n; Wi-Fi Security Standards: WEP, WPA/WPA2 PSK, 802.1x EAP: PEAP/MSCHAPV2, PEAP/GTC, TLS, TTLS/PAP, TTLS/MSCHAP, TTLS/MSCHAPV2, TTLS/GTC, PWD |
| PERSONAL AREA NETWORK (WPAN) | Bluetooth® wireless technology v4.0 - Dual Mode (Classic Bluetooth wireless technology and BLE available) |
| NFC COMMUNICATION | NFC communication between device and cradle |

DECODING CAPABILITY

| | |
|--------------------|--|
| 1D / LINEAR CODES | Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. |
| 2D CODES | Aztec Code, Data Matrix, MaxiCode, PDF417, MicroPDF417, Micro QR Code, QR Code |
| POSTAL CODES | Australian Post, Japanese Post, KIX Code, Royal Mail, USPS Intelligent Mail, USPS PLANET, USPS POSTNET |
| DIGITAL WATERMARKS | Supports Digimarc® Barcode |

ELECTRICAL

| | |
|-------------------|---|
| BATTERY | Replaceable battery pack with rechargeable Li-Ion batteries; 3.7 V; 3,000 mAh (12 Watt-hours) |
| WIRELESS CHARGING | Two charging options: Fast charging or Standard charging |

ENVIRONMENTAL

| | |
|-----------------|---|
| DROP RESISTANCE | Withstands repeated drops from 1.2 m / 4.0 ft onto plywood and 1.5 m / 5.0 ft onto plywood with the rubber boot accessory |
| TEMPERATURE | Operating: -10 to 50 °C / 14 to 122 °F |

INTERFACES

| | |
|------------|---|
| INTERFACES | USB 2.0 Client (with standard Micro-USB connector) SDXC card slot (not user accessible) |
|------------|---|

USER INTERFACES

| | |
|---------------------|--------------------------|
| ACCELEROMETER | 3-Axis accelerometer |
| SOFTSPOT TECHNOLOGY | Virtual trigger/scan key |
| TRIGGER | Pistol-grip models only |
| VIBRATION | Software programmable |

PHYSICAL CHARACTERISTICS

| | |
|-----------------------|---|
| COLOR CUSTOMIZATION | Top case and battery covers (both handheld and pistol-grip models) and Scan Trigger (pistol-grip models) are available in various standard or custom colors |
| COLORS (STANDARD) | Enclosures: Light Grey and Dark Grey Battery Covers: Blue, Red, Green, Orange, Yellow, Light Grey |
| DISPLAY | 4.3 inch full touch TFT-LCD color display; FWVGA: 854 x 480 pixels; 16M colors, LED backlight |
| TOUCH SCREEN | Capacitive, multi-touch, Gorilla® Glass 3 |
| PHYSICAL KEYS | Handheld: Home/scan fully programmable key Pistol-Grip: Home/scan fully programmable key, Scan Trigger key |
| LIGHTING | Software programmable, lights at the bottom of the battery cover |
| DIMENSIONS | Handheld: 14.5 x 7.7 x 3.4 cm / 5.7 x 3.0 x 1.3 in Pistol-Grip: 14.5 x 7.7 x 11.6 cm / 5.7 x 3.0 x 4.5 in |
| WEIGHT (WITH BATTERY) | Handheld: 275.0 g / 9.7 oz Pistol-Grip: 305.0 g / 10.7 oz |

READING PERFORMANCE

| | |
|--------------------|--|
| DEPTH OF FIELD | 4.3 to 35.0 cm / 1.7 to 13.8 in, depending on bar code density |
| MINIMUM RESOLUTION | Linear codes at 4 mils; 2D codes at 5 mils |
| READING INDICATORS | Loudspeaker (Polyphonic); Datalogic's patented 'Green Spot' technology for visual good-read feedback |

SAFETY & REGULATORY

| | |
|--------------------------|---|
| AGENCY APPROVALS | The product meets necessary safety and regulatory approvals for its intended use. |
| ENVIRONMENTAL COMPLIANCE | Complies to EU RoHS |

SOFTWARE

| | |
|---|---|
| CONFIGURATION AND MAINTENANCE DEVELOPMENT | Datalogic X Platform Configuration Utility (DXU) Java and Xamarin SDK available |
|---|---|

SYSTEM

| | |
|------------------|--|
| MEMORY | System RAM: 2 GB; System Flash: 16 GB Flash Disk SD Card: Factory installed option |
| CPU | Qualcomm SnapDragon Quadcore 1 GHz |
| OPERATING SYSTEM | Google Android 6.0 Marshmallow (field upgradeable to Android 7.1 Nougat) |

WARRANTY

| | |
|----------|-------------------------|
| WARRANTY | 1-Year Factory Warranty |
|----------|-------------------------|



Caution: Laser Radiation - do not stare into beam

ACCESSORIES

Cradles and Holders



- 91ACC0043 3-Slot Cradle-Wall Mount
- 91ACC0069 3-Slot Cradle-General Purpose
- 91ACC0072 Single Slot Cradle Locking
- 91ACC0073 Single Slot Cradle Charge only

Miscellaneous



- 91ACC0047 Trolley Holder (60 pcs)
- 91ACC0079 Rubber Boot
- 91ACC0080 Holster
- 91ACC0036 Lanyard