

Go further than you ever could with a smartphone. The new PA726 rugged handheld computer can revolutionize the way you do business. Featuring Android 7.1.2 for the most up-to-date Android experience, it combines the form factor of a 4G dual SIM card smartphone with the performance of an enterprise handheld computer. Stylish and intuitive along with an integrated 1D/2D barcode scanner, the PA726 is a versatile data collection tool for every need in the enterprise solutions.

Powerful Android 7.1.2 Platform

- The First 4.7 inch Android 7.1.2 rugged mobile computer
- Advanced 64-bit octa-core CPU (2GHz) with 3GB RAM and 32GB ROM
- 2GB of ROM is completely independent partition that delivers stable processes and flexible programs installation

Advanced Touchscreen Technology

- 4.7 inch Gorilla Glass 3 touchscreen with 7H hardness to keep it scratch free
- The sunlight-readable screen facilitates outdoor use without draining the battery.

Superior Data Collection

- Integrate 1D/2D barcode scanner with downwards scanning angle design
- High resolution 16MP full HD rear camera and 5 MP front camera

Sheer Durability

- 1.5M drop-resistant housing (1.8M drop-resistance with bumper)
- IP65 (IP67 Optional) heavy-duty protection against water and dust
- Rugged pogo-pin design protects the handheld from the wear and tear of frequent charging and docking.

Multiple Connectivity

- Leading 4G dual SIM card enterprise handheld computer
- Support WLAN: Dual Bands with fast roaming & WWAN: 2G/3G/4G LTE with full bands

User-Friendly Functionality

- Easy Hot-swap battery design without downtime
- Support MDM Software Solutions and utilities such as Airwatch, SOTI, 12Management and MoboLink





PA726 Specifications



System Features

CPU Qualcomm MSM8953, 2GHz Octa Core

Processor, ARM A53 64bits

3 GB RAM Memory 32 GB Flash

MicroSD, up to 128 GB Expanded slot

Android 7.1.2

Languages support English, Thai, Simplified / Traditional Chinese,

Japanese, Spanish, German, French, Italian, Portuguese, Korean and multiple languages

Display

Gorilla Glass 3 with 5-point Capacitive Touch Panel 4.7" Color LCD 1280X720 High Resolution Display 450 cd/m² Brightness

4 Function Keys, Push-to-talk key, Volume up/down key, Left/right scan key, Power key

Indicator

3 color LED to indicate charge, scan and message Vibrator

Symbologies

1D CCD UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 Full ASCI, Code 93, Code 32, Interleaved & Std. (Optional)

2 of 5, EAN 128, Code 11, MSI/Plessey, Code 128, RSS Expended, RSS Limited, RSS14

PDF417, MicroPDF417, Composite, RSS, 2D Imager

TLC-39, Datamatrix, QR Code, Micro QR Code, Aztec, MaxiCode, Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal

Dutch Postal (KIX), and all 1D barcodes

DPM (Optional)

Audio

Speaker 85 dB at 10cm, 3.5mm Audio Jack, Receiver, Microphone*2

Direct-Part-Marked barcodes





Headquaters

http://www.ute.com e-mail:info@hq.ute.com

unitech America

Los Angeles

http://us.ute.com e-mail: info@us.ute.com http://can.ute.com info@can.ute.com

http://latin.ute.com e-mail:info@latin.ute.com

unitech Asia Pacific & Middle East

http://apac.ute.com info@apac.ute.com / info@india.ute.com

http://mideast.ute.com info@mideast.ute.com

Communication

Camera and Flash Light 16 MP Rear, 5 MP Front camera Bluetooth Bluetooth 4.1 BLE Class 2 Supported

Interface USB 2.0 w/ Pogo Pin USB USB 2.0 host / client

WLAN IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/v, support fast roaming WWAN 2G - GSM: GSM850, EGSM900, DCS1800, PCS1900

3G - UMTS: Band 1, Band 2, Band 5, Band 8

4G -LTE: FDD Band 1(2100), Band 2(1900), Band 3(1800), Band 4(1700), Band 5(850), Band 7(2600), Band 8(900), Band

20(800)

TDD: Band 38(2600), Band 39(1900), Band 40(2300), Band

41(2500), Micro SIM slot *2

GPS GPS/ GLONASS RFID/HF Frequency: 13.56MHz

Tag Support: ISO/IEC15693, ISO/IEC14443A, ISO/IEC14443B

Support NFC

Power Source

Extended battery

Main Battery Rechargable Li-ion Battery (Hot Swappable)

Typical 3.6V 3220mAh Minimum 3.6V 3120mAh Typical 3.6V 4800mAh

Minimum 3.6V 4660mAh

Enclosure

Weight 287g with standard battery Dimension 171.3mm x 29.3mm x 80mm

Environmental

Operating temperature -4°F to 122°F (-20°C to 50°C) -22°F to 140°F (-30°C to 60°C) Storage temperature Relative Humidity 5% ~ 95% (Non-Condensing) Drop test to Concrete 1.5 meter, 1.8 meter with bumper

IP65 (IP67 Optional) **Environmental Sealing**

Vibration and Shock test MIL-STD-810G, 514.4 Process II

Regulatory Approvals

CE, FCC, NBTC, NCC, BSMI, VCCI, CCC, RoHS compliance

Accessories

4-slot Ethernet Cradle USB Holder Cable

4-slot Terminal Charging Cradle Hand Strap w/ or w/o stylus loop

1-slot USB Cradle Stylus & Coiled Strap

1-slot Ethernet Cradle Bumper 4-slot Battery Charger Gun Grip Vehicle Charger Wrist-arm Mount Tempered Glass Screen Holster with Belt Strap

unitech Europe

Tilburg / Netherlands

http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan

Tokyo

http://jp.ute.com e-mail:info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com



02/18 Rev.B(2)



PA726

Software Solution

Introduction

It's time to make the most of your unitech hardware. Experience a host of software solutions tailored for the needs of your enterprise.

Whether it's managing a deployment of unitech handhelds in the field or using a 3rd party app to unite all of your devices, Unitech can help you get more out of your investment. The possibilities are endless.

unitech also offers customized solutions and software for business needs. Please contact us for more information.



Solutions



Connect your devices to an IoT platform to collect data from devices and exchange with other systems via RESTful APIs. A web management portal enable managing devices and data easily.

Library



Programmable keys

Provide an easy way to flexibly define the function of each Android keypads.



Smart Device program

Apply IFTTT concept to define actions while a certain condition happens. (powered by Macrodroid)



Silent OS update

Zero touch updates enable OS updates remotely and concurrently.

Compliant APPs



SOTI



TeamViewer

Utilities



12Manage

A light-weight device management tool to allow you updating application to multiple devices at a time and give you insight into the state of all the devices you deploy.



Enterprise launcher

Define applications on the Launcher to avoid users changing settings or using any other applications not for work.



Scanner configuration

Configure all scanner settings with friendly user interface and enable the service to make scanning data as keypad input.



Enterprise configuration

Allow enterprise configurations such as disabling welcome page and specifying applications which will automatically run after boot up

^{*}All trademarks and registered trademarks are the property of their respective owners.